

SANS DIGITAL TowerRAID TR8X6G

8-Bay 6G SAS / SATA Modularize SAS JBOD Storage



The TowerRAID TR8X6G is a 8-bay tower with two mini-SAS connections, for high transfer rates of up to 1,000MB/s bandwidth when used with a high performance RAID controller card. Utilizing high bandwidth mini-SAS (SFF-8088) cabling, the TR8X6G supports 6Gb/s SAS or SATA hard drives to deliver superior read / write speeds that are crucial in performance-driven environments such as video editing industry and server application. The mini-SAS ports combine eight hard drives connections into two, reducing possible points of failures, while preserving uninterrupted data transfer. The TR8X6G also supports SATA drives, allowing users the option to choose between high performance and high capacity storage solutions. Hard drive and RAID controller bundles options are available. When utilizing a SAS or SATA RAID controller, the unit could effortlessly support multi-streaming of compressed high-quality playback or a single-stream of uncompressed 10-bit high definition video under various RAID modes.



Feature

- Eight 3.5-inch SAS or SATA hard drives to SFF-8088 mini-SAS interfaces.
- Accesses eight hard drives using only two cables.
- Modularize design, 8 x hot-swappable trays.
- Supports JBOD, spanning, RAID 0, 1, 1+0, 5, 6 with spare via RAID controller card.

- Supports Areca, Adaptec, ATTO, Dell, LSI, and Intel SAS RAID or SATA RAID controller cards.
- Cable-less backplane design supporting hot-swappable SATA and SAS hard drives.
- Supports plug & play for easy installation.
- Compact enclosure with dust-free cover.
- 250 watts power supply (90V to 264V).
- Supports PC, MAC and Linux. (Please check HBA or RAID controller driver compatibility.)

Specification

Model

TR8X6G

Form Factor

Compact Tower

HDD Trays

8 Hot-Swappable 3.5"

RAID Level

JBOD (RAID Supported via Controller Card)

Maximum Capacity

48TB

Compatible RAID Card

Areca, ATTO, Intel, LSI, Adaptec, Dell, HighPoint

Host Interface & Transfer Rate

Mini-SAS (SFF-8088) x 2

Drive Interface

8 x 3.5" SATA or SAS

Cooling Fan

4.7" Ball Bearing

Power Supply

250W (90V-264V)

Status Indicators

Status and Power LEDs

Dimension (in)& Weight (lb)

5.9"W x 13.4"H x 13.4"D & 13 lb

Safety Regulations

CE, FCC, UL, RoHS

Limited Warranty

2 years